华为云 Paraview Enterprise API 安装指南

先决条件

建筑学

- 具有管理权限的华为云账户
- 默认 VPC 或具有公共子网的 VPC
- 必要的区域访问权限和资源。

VPC		AZ2			
AZ1		·	/	Users	Application 1
Users	EC2		IGW		Application 2
			Interr	net 🦲	Resource 1
Application 2 Application 1		AZ3			Resource 2
Resource 2 Resource 1	Para IAM / Other IAM solutions	·			

步骤 1:基础设施检查

1. 启动华为云控制台,选择要部署到的地域。至少有一个可访问互联网的默认专有网络 (VPC) 或 自定义专有网络 (VPC)。

第2步:通过 KooGallery 市场安装

1. 请打开您的浏览器。我们推荐使用 Chrome 浏览器,并<u>KooGallery 市场。</u>

- 2. 搜索Paraview软件,你会看到一些软件。请点击 Paraview 多因素身份验证器。
- 3.选择您的安装地区,点击订阅,并同意协议。
- 4. 按照说明输入 RFS 堆栈名称。以及管理密码。

Select Template 3 Configure Parameters 3 Configure Stack 4 Confirm Configurations * Stack Name paraview-pare-stack							
* Stack Name paraview-pam-stack The stack name must start with a letter and can contain a maximum of 128 characters, including letters, digits, underscores (_), and hyphens (-). The stack name must be unique.							
Description Paraview part for HCL							
Configure Parameters							
Parameter Value Type Description							
* admin_password 💮 💿 string the admin password of ecs.							
vpc_cidr 192.168.0.0/16 string Specifies the range of available subnets in the VPC. The value ranges from 10.0.0.08 to 10.255.255.0/24,							
vpc_subnet_cidr 192.168.10.024 string Specifies the network segment on which the subnet resides. The value must be in CIDR format and within							
vpc_subnet_gateway_ip 192.168.10.1 string Specifies the gateway of the subnet. The value must be a valid IP address in the subnet segment. Changin							
* charging_mode v string Specifies the charging mode of the disk. The valid values are as follows prePaid: the yearly/monthly billing							
period_unit v string The period unit of the pre-paid purchase. Valid values are month and year. This parameter is mandatory if c							
period 1 number The period number of the pre-paid purchase. If period_unit is set to month , the value ranges from 1 to 9. If							
).							
< Create Stack							
Select Template — Configure Parameters — 3 Configure Stack 4 Confirm Configurations							
Agency huaweicloud							
An agency can clearly define RFS's operation permissions (such as creation, update, and deletion) on stack resources. If the agency permissions are insufficient, subsequent operations such as deployment execution plan creation may fail. Create Agency on IAM							
Recommended. If no agency is configured, RFS will have the permissions of the current user for deployment. An agency limits RFS's permissions on cloud service resources, preventing undesired operations caused by incorrect templates or parameters.							
Auto-Rollback If auto-rollback is enabled, the stack automatically rolls back to the previous successful resource status when the operation fails. After the stack is created, you can modify the stack configurations of its details page.							
Deletion Protection Deletion protection prevents the stack from being deleted accidentally. You can modify it on the stack details page.							

MUAWE	HUA	WEI CLOUD Conso	le ♥ AP-Singapore ∨			Q Search for	More 🗋 😨 🌐 Intl-I	EN paraglobal
Ξ	<	Create Stack						
٢	\bigcirc) Select Template (Configure Parameters ——— (Configure Stack	c Confirm Config	urations		
M	0	RFS is free of charge, but the n	esources in the stack are not. Currently, you	need to create an exe	cution plan (free of charge) to obtain t	he estimated price.		
0		Template Info						
۵ ۵		Stack Name	paraview-pam-stack			Description	Paraview pam for	HCL
Ø		Parameters 🖉						
æ		Parameter Name	Value	Туре	Description			
&		admin_password		string	the admin password of ecs.			
		vpc_cidr	192.168.0.0/16	string	Specifies the range of available sub	onets in the VPC. The value rang	ges from 10.0.0.0/8 to 10.255.255	5.0/24, 172.1
		vpc_subnet_cidr	192.168.10.0/24	string	Specifies the network segment on	which the subnet resides. The va	lue must be in CIDR format and	within the CI
		vpc_subnet_gateway_ip	192.168.10.1	string	Specifies the gateway of the subne	t. The value must be a valid IP a	ddress in the subnet segment. C	hanging this
		charging_mode	postPaid	string	Specifies the charging mode of the	disk. The valid values are as fol	lows:prePaid: the yearly/monthly	billing mode
		period_unit	month	string	The period unit of the pre-paid purc	hase.Valid values are month an	d year. This parameter is mandat	ory if chargi
		period	1	number	The period number of the pre-paid	purchase. If period_unit is set to	month , the value ranges from 1	to 9. If perio
		Stack Settings IAM Permission Agency		Auto-Rollba	ick Disabled	Deletion Protec	tion Disabled	
	Estim	nated fee: You can obtain the estin	nated fee after creating an execution plan (fr	ree of charge).		Previous	bate Execution Plan	rectly Deploy Stack

7.

	n Plan	X
1 To preview your re	source billing information, you can cre	eate an execution plan.
* Execution Plan Name	paraview-pam-hcl-stack	
Description	Paraview pam for hcl stack	
		26/255 //
		OK Cancel
< ∣ paraview-pam-stack	s Events Template Execution Plans	Delete Update Template/Parameter
Basic Information Resources Output		
Basic Information Resources Output		Enter a keyword.
Basic Information Resources Output	atus Estimated Price ③	Enter a keyword. Created Description Operatio
Basic Information Resources Output Deploy Execution Plan Name/ID St paraview-pam-hcl-stack e66d9b58-d541-4f8b-a Av	atus Estimated Price ③ allable View Details	Enter a keyword. Created Description Operation Mar 17, 2025 03:31:25 G Paraview pam for hcl Deploy D

1

< paraview-	pam-stack						(Delete Update Template/Parameter	С
Basic Information	Resources	Outputs	Events	Template	Ex	ecution Plans			
						Welcome to Paraview PAM standalone Trial edition. Please wait about 5mins then you should able to access http://119.8.186.23		Enter a keyword. Q	
Name		Туре				with _sysadmin and Admin.123 credential.	Description		
info		string				Welcome to Paraview PAM standalone Trial ed			

笔记:请耐心等待。安装过程大约需要5分钟。请检查**输出**作为您的应用程序默认凭证。

步骤3: 故障排除

- 1.开启ECS服务
- 2. 搜索 paraview-pam-standalone-trial-hcl vm
- 3. 从操作远程登录

Logging In to a Linux ECS ⑦	
Ensure that the security groups allow access to port 21, 22, 80, 443, 3389 and ICMP. View port functions Configure security group rules	
CloudShell-based Login (Default Port: 22) Recommended You can copy and paste commands, manage multiple sessions, and log in to multiple ECSs easily.	
✓ Other Login Modes	
CBH-based Login VNC Login	

 \times

If you have any remote login issues, you can troubleshoot them based on the help documentation. View FAQs [

1	1		
	T	٠	

5.

• Region :	ap-southeast-3	Refresh
• ECS :	paraview-pam-standalone-trial-hcl	
	 119.8.186.23 (EIP) 192.168.10.235 (Private IP) 	
Port :	22	
• User:	root	1
Auth-Type :	Password-based	
Password :		
Session Name ·	netetiin yoon denned admini password	
	100(@119.8.186.23	
V Open Remo	te Host Filesystem	
Note:	a security of the connection the system will automatically disconnect sessions that have no	t heen
active for more	e than 20 minutes.	t been
- Please make default port 22	sure to add inbound rules to allow external network traffic from CloudShell Proxy Server (SS t) to be sent to the ECSs in the security group.	SH
- When operat	ions get stuck after remote login, please check the CPU and memory of the machine. Please	e
- Huawei Clou	<u>d Eye</u> to send alarm notifications when abnormal ECS events occur. dShell will not save your password, please keep it properly.	
	Connect	

6.#tail -f /var/log/cloud-init-out.log 获取安装详细信息。